



ONE GEL®

Ready to use re-enterable single component silicone gel for insulation and filling



Ready to use
ONE GEL® is already cross-linked and supplied in cartridges suitable for the most common silicone guns for a fast application without waste



Applications

- Filling of electrical junction boxes
- Electrical connections 0,6/1 kV insulation
- Electronic devices and boards insulation
- Designed for applications with hard to reach enclosures or connections
- Ideally suitable for vertical or upended applications
- Applicable in a wide range of sectors: civil, industrial, navy, aviation, automotive

ref.	item	volume (liters)	min. ord. qty.	mult. ord. qty.
ONEGEL	ONE GEL	0,3	24	24

Dielectric strength
25 kV/mm

Colour
light blue

Operating temperature range
-60 °C to +200 °C

Resistivity (IEC 60093)
10 GΩ/mm

Penetration (ISO 2137)
300 mm / cono da 100 g

Density (ISO 3219)
0,97 g/l

Volume reduction
< 0,01%



Ready to use
No component to mix



IP68 SOLUTION
with JuBox
(p. 52)



Vertical
application



High electrical
insulation



High protection from
moisture



Re-enterable
and removable



Unlimited shelf life



Non-irritant



Odourless and
without solvents



Directive
EU 2015/863 (RoHS 3)
Compliant



Halogen free



Eco friendly



NON HAZARDOUS
European Regulationn.
1272/2008 (CLP)