

# AQM 65

## Specification Sheet

### Near reference real-time monitor for ambient air pollutants

The AQM 65 is a fully integrated, temperature-controlled air quality monitoring station that delivers 'near reference' levels of performance in real-time for multiple gases, particulate matter and environmental parameters.

Continuously measure air pollutants including O<sub>3</sub>, NO<sub>2</sub>, NO<sub>x</sub>, CO, SO<sub>2</sub>, VOC, H<sub>2</sub>S, CO<sub>2</sub>, CH<sub>4</sub>, PM<sub>1</sub>, PM<sub>2.5</sub>, PM<sub>4</sub>, PM<sub>10</sub>, TSP, noise and meteorological parameters.



#### What is it?

- A near-reference air quality station with proven long-term performance in extreme climates with advanced temperature control
- Suitable for mobile monitoring applications
- Compatible with a wide range of sensors including noise, black carbon and met sensors all viewed in one data platform
- Includes two-way communications for remote troubleshooting, software upgrades, and remote calibration
- Enables automatic scheduling of calibrations with optional integrated calibration system
- Provides real-time alerts of exceedances via configurable email / SMS alerts

#### What can it measure?

- Multiple gaseous and particulate fractions, wind, weather and noise



#### Who is it for?

- Regulatory authorities who need to extend their ambient air monitoring networks while managing capital and operating expenditure. Particularly suited for:
  - Urban networks
  - Rural/background sites
  - Roadside air monitoring
  - Mobile monitoring
- Environmental consultants and researchers who need to monitor multiple environmental parameters with high data quality, especially in extreme climates
- Industrial operators who need a cost-effective and robust solution to monitor fugitive air emissions for compliance or ESG reporting
  - Industrial perimeter monitoring
  - Oil and gas facilities
  - Quarry and mine operators
  - Port and bulk handling authorities
  - Waste management sites

# Specifications | AQM 65

Particle module		Sizes	Range	Accuracy	Display Resolution	Lower Detectable Limit (2σ)	
Nephelometer		PM <sub>1</sub> , PM <sub>2.5</sub> , PM <sub>10</sub> OR TSP	0 to 60,000 µg/m <sup>3</sup>	±(2 µg/m <sup>3</sup> + 5% of reading)	0.1 µg/m <sup>3</sup>	<1 µg/m <sup>3</sup>	
PCX <sup>1</sup>		PM <sub>1</sub> , PM <sub>2.5</sub> , PM <sub>4</sub> , PM <sub>10</sub> and TSP	0 - 30,000 µg/m <sup>3</sup>	< 5% of reading	0.1 µg/m <sup>3</sup>	0.1 µg/m <sup>3</sup>	
Gas module	Range	Display Resolution	Noise Zero; Span % of reading	Lower Detection Limit (2σ)	Precision	Linearity (% of FS)	Drift 24 hour Zero; Span % of FS
Ozone O <sub>3</sub>	0-500 ppb	0.1 ppb	<1 ppb; 1%	<1 ppb	2% of reading or 2 ppb	1%	1 ppb; 0.2%
Nitrogen dioxide NO <sub>2</sub>	0-500 ppb	0.1 ppb	<1 ppb; 1%	<1 ppb	2% of reading or 2 ppb	1.5%	1 ppb; 0.2%
Carbon Monoxide CO	0-25 ppm	0.001 ppm	0.02 ppm; 1%	0.04 ppm	3% of reading or 0.05 ppm	1%	0.14 ppm; 2%
Sulfur Dioxide SO <sub>2</sub>	0-10,000 ppb	0.1 ppb	1 ppb; 0.02%	2 ppb	0.14% of reading	0.6%	1 ppb; 0.3%
Nitrogen Oxides NO <sub>x</sub>	0-500 ppb	0.1 ppb	<1 ppb; 1%	1 ppb	3% of reading or 3 ppb	1%	1 ppb; 0.2%
Hydrogen Sulfide H <sub>2</sub> S	0-5,000 ppb	0.1 ppb	1 ppb; 0.1%	2 ppb	1% of reading or 3 ppb	0.5%	<1 ppb; <0.5%
Carbon Dioxide CO <sub>2</sub>	0-2000 ppm	1 ppm	5 ppm; 1%	10 ppm	3% of reading or 10 ppm	2%	1 ppm; 0.6%
VOC (Low range)	0-500 ppb	0.1 ppb	<1 ppb 1%	<1 ppb	2% of reading or 1 ppb	1%	1 ppb; 1%
VOC (High range)	0-30 ppm	0.01 ppm	<0.1 ppm; 1%	<0.1 ppm	2% of reading or 0.05 ppm	2%	0.1 ppm; 1%
Methane CH <sub>4</sub>	0-500 ppm	0.01 ppm	0.02 ppm; 0.3%	0.04 ppm	0.4% of reading	<1%	0.04ppm; 1%
System Specifications							
Control system	Embedded fanless PC (Intel Celeron® N3350, 1.1 GHz, dual core, 4 GB RAM, 32 GB SSD hard drive), Debian Linux Operating System						
Communications <sup>2</sup>	Standard: WIFI, Ethernet (LAN) Optional modem: Cellular 3G or 4G LTE						
Software	Talk to our sales team to learn more about Aeroqual Cloud plans.						
Data logging	32 GB Hard Drive (> 5 years data storage)						
Averaging period	1 min, 5 min, 10 min, 15 min, 20 min, 30 min, 1 hr, 2 hr, 4 hr, 8 hr, 12 hr, 24 hr						
Power requirements <sup>3</sup>	90 - 264 Vac, 47 - 63 Hz Typical draw: 100 W (depends on configuration and ambient temperature)						
Enclosure	Outer: IP65 rated aluminum skin with solar reflective coating Inner: 40 - 50 mm (1.6 - 2") layer of cross-linked PE foam insulation. External temperature and relative humidity sensor.						
Gas sampling system	Inlet: Teflon, glass-coated stainless-steel Pump: 12 V brushless DC diaphragm						
PM sampling system	Inlet: Omni-directional 36 cm (14.1 inches) heated inlet; Optional sharp cut cyclones for PM <sub>10</sub> , PM <sub>2.5</sub> or PM <sub>1</sub> size selection Pump: 12 V brushless DC diaphragm						
Dimensions <sup>4</sup>	Standard: 1310 H x 510 W x 280 D mm (51½" H x 20" W x 11" D)						
Weight <sup>5</sup>	< 30 kg						
Operating range	-35 °C to +50 °C (-31 °F to 122 °F)						
Mounting	Mounting brackets included						
47mm sample filter <sup>5</sup>	47 mm filter for particle loading analysis						
Factory integrated sensors <sup>5</sup>	Gill WindSonic (ultrasonic wind sensor), Vaisala WXT536 (weather transmitter), Cirrus MK427 Class 1 (noise sensor), Novalynx Pyranometer (solar radiation)						
Compatible tested sensors	BSWA 308 (sound level meter), Met-One BC-1060 (black carbon), microAeth MA350 (black carbon), Svantek SV971A (sound level meter)						
Compliance							
In conformity with EC Directives 2014/30/EU and 2014/35/EU; FCC 47 CFR Part 15; RoHS 3 (EU2015/863), REACH							
Certified Modules				MCERTS			
AQM65 PM <sub>10</sub> Nephelometer				Yes - Sira MC160289/02			

<sup>1</sup> Representative values for PM<sub>2.5</sub>; for individual channel performance please see the Aeroqual Technical Performance Guide

<sup>2</sup> 4G LTE not available in all markets

<sup>3</sup> Configuration used for power and weight calculations: base unit, nephelometer, PM<sub>10</sub> sharp cut, modem, heater on

<sup>4</sup> Dimensions are for enclosure. Nephelometer sampling inlet with cyclone adds 360 mm (14.17") to total height. PCX adds 200mm (7.87").

<sup>5</sup> Optional

AQM65 PM<sub>10</sub>

